

J66K - Generating set

J66K Power Products Generating set, equipped with a JOHN DEERE engine and LEROY SOMER alternator.



General characteristics

Mechanic governor
Mechanically welded chassis with antivibration suspension
Main line circuit breaker
Radiator for wiring temperature of 48/50°C max with mechanical fan
Protective grille for fan and rotating parts
9 dB(A) silencer supplied separately
Charger DC starting battery with electrolyte
12 V charge alternator and starter
Delivered with oil and coolant -30°C
Manual for use and installation



Voltage (V)	ESP Power (kWe/kVA)	PRP Power (kWe/kVA)	Back-up power (A)	Dimensions (L. x l. x h.)	Weight
415/240	52.8/66	52.8/66	91	Length : 1870 mm Width : 994 mm Height : 1360 mm	1000 kg net 1210 kg gross
400/230	52.8/66	52.8/66	95		
380/220	52.8/66	52.8/66	100		
200/115	52.8/66	52.8/66	190		
240 TRI	52.8/66	52.8/66	158		
230 TRI	52.8/66	52.8/66	165		
220 TRI	52.8/66	52.8/66	173		
220/127	52.8/66	52.8/66	173		

Hoods

	Model	dB(A)@1m	dB(A)@7m	Dimensions (L. x l. x h.)	Weight	Tank
	M128-DW48	76	76	Length : 2344mm Width : 1060mm Height : 1989mm	1687 kg net 2351 kg gross	700 L
	M128	76	76	Length : 2300mm Width : 1060mm Height : 1680mm	1410 kg net 1610 kg gross	180 L

Standard Control Panel

NEXYS



The NEXYS is a versatile control unit allowing operation in manual or automatic mode. Equipped with an LCD screen, the user-friendly NEXYS offers high-quality basic functions to guarantee simple, reliable operation of your generating set.

Offers the following functions:

Standard electrical measurements: voltmeter, frequency meter, ammeter.

Engine parameters: working hours counter, engine speed, battery voltage, fuel level.

Alarms and faults: oil pressure, coolant temperature, failure to start, overspeed (> 60 kVA), charging alternator fault, low fuel level, emergency stop.

For more information, please refer to the sales documentation.

Optional control panel

TELYS



The highly versatile TELYS control unit is complex yet accessible, thanks to the particular attention paid to optimising its ergonomics and ease of use. With its large display screen, buttons and scroll wheel, it places the accent on simplicity and communication.

The TELYS offers the following functions:

Electrical measurements: voltmeter, frequency meter, ammeter.

Engine parameters: working hours counter, oil pressure, coolant temperature, fuel level, engine speed, battery voltage.

Alarms and faults: oil pressure, coolant temperature, failure to start, overspeed, alternator min./max., battery voltage min./max., emergency stop, fuel level.

Ergonomics: wheel for navigating around the various menus.

Communication: remote control and operation software, USB connections, PC connection.

For more information on the product and its options, please refer to the sales documentation.